



IS930.RG

Tablet



IS-TH1xx.RG

Handheld Barcode Scanner

- › **Operating system**
Android 10
- › **Dimensions**
weight: 890 g
size: 237 x 156 x 22 mm
- › **Display**
8" RugDisplay Glass multi capacitive touchscreen with a resolution of 1200 x 1920 px
- › **Camera**
13 MP AF (rear), 5 MP FF (front)
- › **Wireless communication**
Bluetooth® 5, Wi-Fi®, GPS, A-GPS, GLONASS, Beidou, Galileo, NFC
- › **Processor**
Qualcomm® Snapdragon™ SDM660 Octa Core (2,2 GHz/1,8 GHz)
- › **Memory**
4 GB RAM, 64 GB internal memory, external memory microSD up to 128 GB

- › **Frequencies**
GSM: 850/900/1800/1900 MHz
WCDMA: UMTS B1/2/4/5/8
LTE-FDD: B1/2/3/4/5/7/8/12 with MFBI B13/14/17/20/25/26/28A/28B/29/30/66
LTE-TDD: B38/B39/B40/B41
TD-SCDMA: B34/B39
- › **Battery**
8400 mAh
- › **Safety functions**
SOS key
LWP ready*
- › **Degree of protection**
IP68 dust-/waterproof
MIL-STD 810H
usable from -20 °C to +60 °C

- › **Dimensions**
weight: 500 g
size: 200 x 125 x 82 mm
- › **Indication function**
loudspeaker
vibration
LED display
- › **Communication**
over the multi functional ISM interface

- › **Power supply**
over the connected device, this can be loaded in the Trigger Handle
- › **Scan types**
IS-TH1 MR (mid range)
with Zebra SE4750 MR up to 6 m
IS-TH1 ER (extended range)
with Zebra SE4850 ER up to 18 m



i.safe MOBILE GmbH
i_Park Tauberfranken 10, 97922 Lauda-Koenigshofen, Germany
info@isafe-mobile.com

WWW.ISAFE-MOBILE.COM

*Push-To-Talk/LWP (third party application required)



Rugged Devices





IS330.RG

Mobile Phone



IS530.RG

Smartphone



IS655.RG

Smartphone

- › **Operating system**
Android 10
- › **Dimensions**
weight: 318 g
size: 152,8 x 62 x 26,7 mm
- › **Display**
2,6" Gorilla®Glass, 3. generation
with a resolution of 320 x 432 px
- › **Camera**
13 MP AF (rear), 5 MP FF (front)
- › **Wireless communication**
Bluetooth® 5, Wi-Fi®, GPS, A-GPS,
GLONASS, Beidou, Galileo, NF
- › **Processor**
Qualcomm® Snapdragon™ SDM660
Octa Core (2,2 GHz/1,8 GHz)
- › **Memory**
4 GB RAM, 64 GB internal
memory, external memory microSD
up to 128 GB

- › **Frequencies**
GSM: 850/900/1800/1900 MHz
WCDMA: UMTS B1/2/4/5/8
LTE-FDD: B1/2/3/4/5/7/8/12
with MFBI B13/14/17/20/25/26/28A/
28B/29/30/66
LTE-TDD: B38/B39/B40/B41
TD-SCDMA: B34/B39
- › **Battery**
4050 (typ. 4200) mAh,
replaceable
- › **Safety functions**
SOS key, PTT key
LWP ready*, PTT ready*
- › **Degree of protection**
IP68 dust-/waterproof
MIL-STD 810G
usable from -20 °C to +60 °C

- › **Operating system**
Android 10
- › **Dimensions**
weight: 325 g
size: 155 x 80 x 25 mm
- › **Display**
4,5" Gorilla®Glass with a
resolution of 854 x 480 px
- › **Camera**
13 MP AF (rear), 5 MP FF (front)
- › **Wireless communication**
Bluetooth® 5, Wi-Fi®, GPS, A-GPS,
GLONASS, Beidou, Galileo, NFC
- › **Processor**
Qualcomm® Snapdragon™ SDM660
Octa Core (2,2 GHz/1,8 GHz)
- › **Memory**
4 GB RAM, 64 GB internal
memory, external memory microSD
up to 128 GB

- › **Frequencies**
GSM: 850/900/1800/1900 MHz
WCDMA: B1/2/4/5/8
LTE-FDD: B1/2/3/4/5/7/8/12 with MFBI
B13/14/17/20/25/26/28A/28B/29/30/66
LTE-TDD: B38/B39/B40/B41
TD-SCDMA: B34/B39
- › **Battery**
3600 mAh, replaceable
- › **Quick charge**
- › **Safety functions**
SOS key, PTT key
LWP ready*, PTT ready*
- › **Degree of protection**
IP68 dust-/waterproof
MIL-STD 810G
usable from -20 °C to +60 °C

- › **Operating system**
Android 10
- › **Dimensions**
weight: 203 g
size: 152,5 x 75,4 x 12,5 mm
- › **Display**
5,5" HD+ capacitive touchscreen
with a resolution of 720 x 1440 px
- › **Camera**
13 MP (rear), 8 MP (front)
- › **Wireless communication**
Bluetooth® 5, Wi-Fi®, GPS, A-GPS,
GLONASS, NFC
- › **Processor**
Helio P22 (MT 6762V)
- › **Memory**
3 GB RAM, 32 GB internal memory,
external memory microSD
up to 128 GB

- › **Frequencies**
GSM: B2/3/5/8
WCDMA B1/5/8
FDD LTE B1/3/5/7/8/20/28A/28B
TDD LTE B38/40/41, (120M)
- › **Battery**
4200 mAh, integrated
- › **Dual nano-SIM**
- › **Safety functions**
PTT key
PTT ready*
- › **Degree of protection**
IP68 dust-/waterproof
MIL-STD 810G
usable from -20 °C to +60 °C

*Push-to-talk/LWP (third party application required)