

i.safe MOBILE

CL I DIV 2



**Remote Speaker
Microphone**

PTT Push-To-Talk

**13-pin ISM
interface**

IS-RSMG2.2

The wired remote loudspeaker microphone is specially designed for PTT applications and has NEC500 Class I Div 2 (Northern America) approval. With its robust but lightweight housing and the secure ISM interface, this device is an ideal addition to our mobile devices IS330.2 and IS530.2. The dynamic loudspeaker is specially designed for noisy environmental conditions.

› All trademarks and copyrights are the properties of their respective owners. › © 2021 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | X181MD01REV01_EN_12.2021



i.safe MOBILE

< IS-RSMG2.2 >



NEC500 approval:
Class I Div 2 Groups A, B, C, D, T4

TECHNICAL FEATURES

| | |
|---------------------------|---|
| Loudspeaker | Dynamic 3-stage volume control Sensitivity: 93 dB (1 mW) Bandwidth: 50 Hz to 8 kHz |
| Microphone | Electret Omni-Directional Sensitivity: -38 dB \pm 3 dB (1 kHz) Bandwidth: 50 Hz to 16 kHz |
| Measurement | Size: 98,11 x 65,93 x 26,96 mm Weight: 212 g |
| Power supply | Over the connected device |
| Cable length | flexible spiral cable from 48 to 130 cm |
| Connection | ISM interface |
| Type of protection | IP54 Operation range from -20 °C up to +60 °C |

SET CONTENT

Remote Speaker Microphone, Quick Start Manual and Safety Instructions

Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.

WWW.ISAFE-MOBILE.COM

EN